

ADVA® CAST 593

High Range Water Reducing Admixture

DESCRIPTION

ADVA® Cast 593 is a high efficiency, low addition rate polycarboxylate-based high-range water reducer designed for the production of a wide range of concrete mixes, from conventional to Self-Consolidating Concrete (SCC). It is designed to impart extreme workability without segregation to the concrete.

ADVA® Cast 593 admixture is supplied as a ready-to-use liquid that weighs approximately 1.1 kg/L (9.0 lbs/gal). It does not contain intentionally added chlorides.

ADVANTAGES

- Excellent dosage efficiency, moisture control and air control
- Fast dispersion "wet-out"
- Enhanced concrete cohesiveness with low viscosity for rapid placement
- Superior finish on cast surfaces
- Excellent strength development

Method of Use

Dosage

- ADVA® Cast 593 is an easy to dispense liquid admixture. Dosage rates can be adjusted to meet a wide spectrum of concrete performance requirements. Addition rates can vary from 130 to 650 mL/100 kg (2 to 10 fl oz/100 lbs) with the type of application, but will typically range from 200 to 390 mL/100 kg (3 to 6 fl oz/100 lbs) of cementitious.
- Should conditions require using more than the recommended addition rate, please consult your representative.
- Mix proportions, cementitious content, aggregate gradations and ambient conditions will affect admixture dosage requirements. If materials or conditions require using more than the recommended addition rates, or when developing mix designs for Self-Consolidating Concrete please consult your representative for more information and assistance.

Additional Usage Recommendations

- ADVA® Cast 593 high-range water reducer that is formulated to impart improved workability to the concrete and to achieve high early compressive strength as required by the precast industry. It can be used for the production of Self-Consolidating Concrete in precast/prestressed applications and may be used in conventional concrete production.
- ADVA® Cast 593 admixture may be used in low water-cementitious ratio applications where concrete stability and improved tolerance to concrete material variability are required.
- It may be used to produce concrete with very low water/cementitious ratios while maintaining normal levels of workability.

Equipment

- A complete line of accurate, automatic dispensing equipment is available.

ADVA® CAST 593

High Range Water Reducing Admixture

Complimentary Products

- ADVA® Cast 593 high-range water reducer is compatible with most admixtures as long as they are added separately to the concrete mix. However, it is not recommended for use in concrete containing naphthalene-based admixtures including DARACEM® 19 and DARACEM® 100 and melamine-based admixtures including DARACEM® 65. In general, it is recommended that the product be added to the concrete mix near the end of the batch sequence for optimum performance. Different sequencing may be used if local testing shows better performance. Please see [Technical Bulletin TB-0110](#), Admixture Dispenser Discharge Line Location and Sequencing for Concrete Batching Operations for further recommendations.
- Pretesting of the concrete mix should be performed before use and as conditions and materials change in order to assure compatibility with other admixtures, and to optimize dosage rates, addition times in the batch sequencing and concrete performance. For concrete that requires air entrainment, the use of an ASTM C260 air-entraining agent (such as DARAVAIR® or DAREX® product lines) is recommended to provide suitable air void parameters for freeze-thaw resistance.

CHARACTERISTICS

| | |
|--|----------------------------|
| Product Nature | Liquid |
| Color | Colourless to light yellow |
| Shelf life | 12 months |
| Cl⁻ ions content | ≤ 0,100 % |
| Specific gravity (25°C) in g/ml | 1,078 |
| pH (25°C) | 3,90 |

PRECAUTIONS

- It will freeze at approximately 0°C (32°F) but will return to full functionality after thawing and thorough mechanical agitation.

SAFETY

Prior to any use, please read carefully the Safety data Sheet.

PACKAGING

- Bulk
- 210L Drum (55 gallons)
- IBC 1000L