

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

1 Identification

Product identifier

Trade name: ***Pieri Duro-Tard 50™***

SDS ID Number: 26

Relevant identified uses of the substance or mixture, and uses advised against
Specialty construction product. Not intended for other uses

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

GCP Applied Technologies
62 Whittemore Avenue
Cambridge, MA 02140 USA

GCP Canada, Inc.
294 Clements Road W.
Ajax, Ontario L1S 3C6 Canada

www.graceconstruction.com

Information department:

Environmental Health & Safety
USA: +1-617-876-1400 (24 hours)
+1-800-354-5414 (8AM - 5PM) Not functional within Massachusetts
CAN: 1-905-683-8561 (24 hours)
In Canada: +1-905-683-8561

Transport Emergency: Chemtrec +1-800-424-9300 (24 hours)

2 Hazard(s) identification

Classification of the substance or mixture

Highly flammable liquid and vapor.

Causes skin irritation.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Label elements:

Hazard pictograms



GHS02



GHS07



GHS08

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

Trade name: *Pieri Duro-Tard 50™*

(Cont. from page 1)

Danger

Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Wear protective gloves / eye protection / face protection.

Take precautionary measures against static discharge.

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Additional information: Avoid breathing dust.**Hazard description:** Flammable**NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

HMIS-ratings (scale 0 - 4)

Health = *2

Flammability = 3

Reactivity = 0

Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**3 Composition/information on ingredients****Chemical characterization: Mixtures****Description:** Mixture of the substances listed below with additional nonhazardous ingredients.**Hazardous components:**

64742-89-8	Solvent naphtha (petroleum), light aliphatic	25-30%
108-88-3	Toluene	10-20%
8052-41-3	Stoddard solvent	0.1-1.0%

Additional information: For the wording of the listed hazard phrases refer to section 16.**4 First-aid measures****Description of first aid measures****General information:**

(Cont. on page 3)

USGHS

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

Trade name: *Pieri Duro-Tard 50™*

(Cont. from page 2)

Get medical advice/attention if you feel unwell.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Immediately wash contaminated skin with soap or mild detergent and water. If this chemical soaks clothing, immediately remove clothing and wash skin.

After eye contact:

Rinse opened eye for several minutes under running water.

Rinse cautiously with water for several minutes.

After swallowing:

Wash out mouth with water

Rinse mouth.

Do not induce vomiting; immediately call for medical help.

Never give anything by mouth to an unconscious person.

Information for doctor:**Most important symptoms and effects, both acute and delayed**

Harmful: may cause lung damage if swallowed.

Irritating to eyes.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

*

5 Fire-fighting measures**Extinguishing media**

Suitable extinguishing agents: CO₂, sand,extinguishing powder. Do not use water.

Special hazards arising from the substance or mixture No further relevant information available.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

*

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Prevent seepage into sewage system, workpits and cellars.

Methods and material for containment and cleaning up:

Contain and/or absorb spill with inert material (i.e. sand, vermiculite) then place in a suitable container.

Sweep up spilled product into receptacles.

Dispose contaminated material as waste according to section 13 of the SDS.

Reference to other sections

See Section 7 for information on safe handling.

(Cont. on page 4)

USGHS

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

Trade name: *Pieri Duro-Tard 50™*

(Cont. from page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage**Handling:****Precautions for safe handling**

Open and handle receptacle with care.

Prevent formation of aerosols.

Flammable mixtures with air can be formed in emptied containers. Do not puncture, cut, drill, heat or weld uncleaned drums.

Avoid contact with skin.

Avoid contact with eyes.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Use only in explosion protected area.

Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Empty containers may retain hazardous residue, both liquid and vapor.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:** Store in a cool location.**Information about storage in one common storage facility:** Use only in explosion protected area.**Further information about storage conditions:** Keep receptacle tightly sealed.**Specific end use(s)** No further relevant information available.**8 Exposure controls/personal protection****Additional information about design of technical systems:** No further data; see item 7.**Control parameters****Components with limit values that require monitoring at the workplace:****108-88-3 Toluene**

PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm

(Cont. on page 5)

USGHS

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

Trade name: *Pieri Duro-Tard 50™*

(Cont. from page 4)

TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm
BEI	

8052-41-3 Stoddard solvent

PEL (USA)	Long-term value: 2900 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 ppm Ceiling limit value: 1800* mg/m ³ *15-min
TLV (USA)	Long-term value: 525 mg/m ³ , 100 ppm

67-56-1 Methanol

PEL (USA)	Long-term value: 260 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV (USA)	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

Ingredients with biological limit values:**108-88-3 Toluene**

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

67-56-1 Methanol

BEI (USA)	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----------	---

Additional information: The lists that were valid during the creation were used as basis.**Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Avoid contact with the eyes and skin.

The usual precautionary measures for handling chemicals should be followed.

Breathing equipment:

A chemical cartridge respirator with organic vapor cartridge is required if occupational exposure limits are exceeded. A dust/mist cartridge or prefilter may be needed in addition to control exposure to mist. Supplied air respirator (SCBA) is required at exposure levels above the capabilities of a chemical cartridge respirator.

Protection of hands:

Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

(Cont. on page 6)

USGHS

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

Trade name: *Pieri Duro-Tard 50™*

(Cont. from page 5)

Material of gloves

Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Eye protection:

Safety glasses with side shield protection.

Safety glasses with side shields should be worn to prevent contact due to splashing. Under high vapor mist concentrations, tightly sealed goggles should be worn.



A face shield should also be worn if there is potential exposure to splash or spray.

Body protection:

Protective work clothing

Use personal protective equipment as required.

Take off contaminated clothing.

*

9 Physical and chemical properties**Information on basic physical and chemical properties****General Information****Appearance:****Form:**

Liquid

Color:

According to product specification

Odor:

Characteristic

Odor threshold:

Not determined.

pH-value (~):

Not determined.

Change in condition**Melting point/Melting range:**

Undetermined.

Boiling point/Boiling range:

110 °C (230 °F)

Flash point:

12 °C (54 °F)

Flammability (solid, gaseous):

Not applicable.

Decomposition temperature:

Not determined.

Auto igniting:

Product is not selfigniting.

Danger of explosion:

In use, may form flammable/explosive vapor-air mixture.

Explosion limits:**Lower:**

1.2 Vol %

Upper:

7.0 Vol %

VOC Content (max):

42.00 %

Vapor pressure at 20 °C (68 °F):

29 hPa (22 mm Hg)

Density: (~) at 20 °C (68 °F)1.1 g/cm³ (9.18 lbs/gal)**Relative density**

Not determined.

Vapor density

Not determined.

Evaporation rate

Not determined.

(Cont. on page 7)

USGHS

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

Trade name: *Pieri Duro-Tard 50™*

(Cont. from page 6)

Solubility in / Miscibility with Water:Not miscible or difficult to mix.
Not miscible or difficult to mix.**Partition coefficient (n-octanol/water):** Not determined.**Viscosity:****Dynamic:**

Not determined.

Kinematic:

Not determined.

Molecular weight

Not applicable.

Other information

No further relevant information available.

* **10 Stability and reactivity****Reactivity** Stable under normal conditions.**Chemical stability****Thermal decomposition:** No decomposition if used according to specifications.**Conditions to avoid** No further relevant information available.**Incompatible materials:** No further relevant information available.**Hazardous decomposition products:**

Carbon monoxide and carbon dioxide

Hydrocarbons

Other potentially hazardous products may also be formed.

Additional information: See section 7 for information on handling, storage and conditions to be avoided.* **11 Toxicological information****Information on toxicological effects****Acute toxicity:****LD/LC50 values relevant for classification:****108-88-3 Toluene**

Dermal	LD50	12124 mg/kg (rabbit)
		5000 mg/kg (rat)

Primary irritant effect:**on the skin:** Irritating to skin.**on the eye:** No irritating effect expected**inhalation:** May cause drowsiness or dizziness.**Ingestion:** Harmful: may cause lung damage if swallowed.**Additional toxicological information:**

Chemicals contained in this product can affect the skin, heart, brain, liver, kidneys, lungs and spleen. Over exposure by inhalation may be fatal due to pulmonary edema (fluid in lungs). This material may be harmful or fatal if swallowed. Ingestion may result in vomiting; aspiration (breathing) of vomitus into lungs must be avoided as even small quantities may result in aspiration pneumonitis. Some harmful effects are also possible through skin absorption.

(Cont. on page 8)

USGHS

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

Trade name: *Pieri Duro-Tard 50™*

(Cont. from page 7)

Carcinogenic categories**IARC (International Agency for Research on Cancer) Human Carcinogenicity:**
Group 1- Positive, Group 2A- Probable, Group 2B- Possible, Group 3- Not Classifiable

108-88-3	Toluene	3
13463-67-7	Titanium dioxide	2B
14807-96-6	Talc	3
7631-86-9	Silicon dioxide, amorphous, chemically prepared	3

NTP (National Toxicology Program)**K–Known to be carcinogenic, R–May reasonably be anticipated to be carcinogenic**

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

*

12 Ecological information**Toxicity****Aquatic toxicity:** No further relevant information available.**Persistence and degradability** No further relevant information available.**Behavior in environmental systems:****Bioaccumulative potential** No further relevant information available.**Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** Danger to drinking water if even small quantities leak into the ground.**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Other adverse effects** No further relevant information available.

*

13 Disposal considerations**Waste treatment methods** Comply with Federal, State and local regulations.**Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:**Recommendation:** Disposal must be made according to official regulations.

USGHS

(Cont. on page 9)

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

Trade name: *Pieri Duro-Tard 50™*

(Cont. from page 8)

*

14 Transport information

UN-Number

DOT, ADR, IMDG, IATA

UN1993

UN proper shipping name

DOT

Flammable liquids, n.o.s. (Solvent naphtha (petroleum), light aliphatic, Toluene)

ADR

Flammable liquids, n.o.s., special provision 640D (Solvent naphtha (petroleum), light aliphatic, Toluene)

IMDG, IATA

FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light aliphatic, TOLUENE)

Transport hazard class(es)

DOT



Class

3 Flammable liquids

Label

3

ADR, IMDG, IATA



Class

3 Flammable liquids

Label

3

Packing group

DOT, ADR, IMDG, IATA

II

Environmental hazards:

Marine pollutant:

No

Special precautions for user

Danger code (Kemler):

Warning: Flammable liquids

EMS Number:

33

F-E, S-E

Transport/Additional information: Not classified as a dangerous good for transport by road, rail or air.

ADR

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

IMDG

Limited quantities (LQ)

1L

Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation":

UN1993, Flammable liquids, n.o.s., special provision 640D (Solvent naphtha (petroleum), light aliphatic, Toluene), 3, II

USGHS

(Cont. on page 10)

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

Trade name: *Pieri Duro-Tard 50™*

(Cont. from page 9)

* 15 Regulatory information

SARA (Superfund Amendments and Reauthorization Act)

Section 302/304 (extremely hazardous substances):

108-88-3 | Toluene

Section 313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):

108-88-3 | Toluene

13.9%

SARA Section 312/Tier I & II Hazard Categories:

Health Delayed (chronic)	Yes
Health Immediate (acute)	Yes
Flammable	Yes
Reactive	No
Pressure	No

North America Chemical Inventory Status

TSCA (Toxic Substances Control Act - United States):

All ingredients are listed or exempt from listing unless otherwise noted below.

CEPA (Canadian DSL):

All ingredients are listed or exempt from listing unless otherwise noted below.

Right to Know Ingredient Disclosure:

471-34-1	Calcium carbonate; limestone powder
	Hydrocarbon petroleum resin
63449-39-8	Paraffin waxes and hydrocarbon waxes
13463-67-7	Titanium dioxide
57-50-1	Sucrose

California Proposition 65

Chemicals known to cause cancer:

Toluene
Titanium dioxide
Quartz (SiO ₂)
Ethylbenzene
1,4-dioxane
Ethylene oxide

Chemicals known to cause reproductive toxicity for females:

75-21-8 | Ethylene oxide

Chemicals known to cause reproductive toxicity for males:

75-21-8 | Ethylene oxide

Chemicals known to cause developmental toxicity:

108-88-3	Toluene
67-56-1	Methanol
75-21-8	Ethylene oxide

Carcinogenicity Categories

EPA (Environmental Protection Agency)

108-88-3 | Toluene

II

TLV-ACGIH (THE American Conference of Governmental Industrial Hygienists)
Human Carcinogen - A1 Confirmed, A2 Suspected, A3 Unknown Relevance, A4 Not Classifiable

Toluene	A4
Titanium dioxide	A4

(Cont. on page 11)

USGHS

Safety Data Sheet

Printing date 06/08/2016

Version Number 1.0

Reviewed on 06/08/2016

Trade name: *Pieri Duro-Tard 50™*

(Cont. from page 10)

Sucrose

A4

Talc

A4

NIOSH-Cancer (National Institute for Occupational Safety and Health)

13463-67-7 | Titanium dioxide

Volatile Organic Compounds (VOC) reported per the Emission Standards. 450.15 g/l / 3.80 lb/gl

*

16 Other information

The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection.

Department issuing SDS:

GCP Applied Technologies
62 Whittemore Avenue
Cambridge, MA 02140 USA
USA: +1-617-876-1400 (24 hours)
+1-800-354-5414

Other Information:

There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis. Therefore preventing the onset of silicosis will also reduce the cancer risk.

Date of preparation / last revision 06/08/2016 / -

The first date of preparation 08/16/2006

Number of revision times and the latest revision date 1.0 / 06/08/2016

USGHS