TECHNICAL DATA SHEET

PIERI® EURO WAX

Release agent



DESCRIPTION

PIERI* **EURO-WAX** is a semi-liquid, high performance visco-elastic form release agent that ensures high quality architectural surfaces. PIERI * EURO-WAX will not stain concrete or affect adhesion of waterproofing or other coatings. Coverage: 120-245 m 2 /L (5,000-10,000 ft 2 /gal).

Method of Use

Dosage

- Apply an extremely thin coat with rag, sponge or mop. Can only be spray applied with airless equipment.
- The usage of PIERI® EURO-WAX results in clean, uniform surfaces with little or no cleanup required.
- Flash Point: 46°C (115°F)

Additional Usage Recommandations

- PIERI® EURO-WAX is formulated for use with the most intricate moulds and forms; especially with no or low draft for release. PIERI® EURO-WAX may be used with all types of forms, including plastic, rubber, latex as well as Styrofoam and is particularly useful in all self-consolidating concrete (SCC) concrete applications.
- PIERI® EURO-WAX is a low odour, viscous liquid that may be used at low and high temperatures.
- It is a non-staining, rain resistant and provides corrosion inhibiting cabability, without creating powdery residue.

CHARACTERISTICS

Shelf life	12 months
Specific gravity (25°C)	0,800

PACKAGING

- 210L Drum (55 gallons)
- 20 L bucket

PRECAUTIONS

 PIERI® EURO-WAX has a shelf life of one year from date of manufacture if stored in in a cool dry place in its closed original container. Keep away from all sources of heat, sparks or flame.

SAFETY

Prior to any use, please read carefully the Safety data Sheet.

